



HTL2 Eco Plus Fuel-Efficient, Long Haul Trailer

Applications: Heavy haul and long haul trailer positions.



Legend:			
3 G	×.	O	Ô
3G Casing	SmartWay Verified	Intelligent Tire	Retread Available
PRODUCT FEATL	IRES ABOVE ONLY APPLY TO	PRODUCTS IF THE MATO	CHING ICON IS DARKENED.

HTL2 Eco Plus Fuel-Efficient, Long Haul Trailer



DATA

		· · · · ·																	~~-	00	ĔĞ
					STATIC		OVERALL		OVERALL		LOADED			MINIMUM		REVS		TIRE		MAX. LOAD @ INFLATION	
TIRE LOA SIZE RAN		ARTICLE NUMBER	TREAD DEPTH		LOADED RADIUS		INFLATED DIAMETER		INFLATED WIDTH		SECTION WIDTH		APPROVED RIM(S)	DUAL SPACING		PER UNIT		WEIGHT		SINGLE	DUAL
SIZE	KANGE	NOWIDER	(32nds)	(MPH)	IN	мм	IN	ММ	IN	ММ	IN	ММ	KIIVI(3)	IN	ММ	МІ	км	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
215/75R17.5	J	05310170000	15	75	14.1	359	30.4	772	8.5	215	9.1	231	6.00, 6.75	9.5	242	681	423	61	28	4805, 125 (2180, 860)	4540, 125 (2060, 860)
235/75R17.5	J	05310180000 * 05650170000 *	13	75	14.5	369	31.6	802	9.2	234	10.0	254	6.75, 7.50	10.6	269	656	407	65	29	6005, 125 (2725, 860)	5675, 125 (2575, 860)
245/70R17.5	J	05310190000 *04650160000 *	13	75	14.5	369	31.6	802	9.2	234	10.0	254	6.75, 7.50	10.6	269	656	407	65	29	6005, 125 (2725, 860)	5675, 125 (2575, 860)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																					

Note - Rim listed first is the measuring rim. 👀 = Intelligent Tire Article #. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change OI inch (25 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

ures & Benefits



Low rolling resistance **compound** provides excellent fuel economy at cool operating temperatures.



Advanced tread design provides long original mileage and low cost per mile.



Heavy ply construction for structural durability in large capacity applications.



Patented groove technology leads to minimum stone retention, extending casing life.

Innovative groove geometry promotes efficient water evacuation, traction and wet braking capabilities throughout tire life.

Applications: Heavy haul and long haul trailer positions.